PRODUCT INFORMATION SHEET

Product Code: **K9940**



Product: Single Side Butyl Cloth Tape

Colour: Black

Roll Size: 6mm to 1200mm in 20 Metre Lengths

Adhesive: Butyl

Description: A black PE coated cloth with an aggressive black butyl based pressure sensitive adhesive. Developed to have an easy tear and unwind for use primarily in the building and construction industry.

Application:

- Forming moisture/vapour seals on membranes (construction & horticulture)
- Patching & joining PE Sheeting and other Low Energy surfaces
- Holding and joining as a permanent repair tape
- Temporary hose repair

Technical Details:

Tape Thickness:	0.35mm
Breaking Load:	51 N/cm
Elongation at Break:	15%
Adhesion to Steel:	7.4 N/cm
Vapour Penetration:	1.0 g/m^2 hrs
Service Temperature:	-10°C to 50°C
Storage Temperature:	15°C to 25°C
Shelf Life:	12 Months

Surface Preparation: The surface on which the tape is to be used must be clean, dry and free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended application temperature is between 15°C and 25°C.

Storage: Tapes stored below the minimum application temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.

Note: The above figures represent average values. Actual figures can vary. The selection and application of a tape is the responsibility of the buyer. Tape should be stored at room temperature and should not be exposed to sunlight. We reserve the right to make changes without notice to our products and specifications.